

VENTURI PROPORTIONER

PRODUCT DESCRIPTION

Dosatron's self-cleaning polypropylene proportioner is chemical resistant and includes a built-in check valve designed to prevent back filling into the concentrate tank. A simple 1/4 turn of the handle changes the function from dosing (ON) to rinsing, and a system of 12 color coded tips are provided for various injection rates. Back flush mode allows for easy cleaning.



PRODUCT SPECIFICATIONS

Dilution Range:	1:100 to 1:2.3 (1% to 43.6%)
Water Flow:	up to 2 GPM in ON mode; up to 13 GPM in Rinse mode
Operating Pressure Range:	7 to 58 PSI
Available Housing Materials:	Polypropylene
Weight:	7.4 oz
Connection Size:	3/4" NPT
Maximum Temperature:	160 ^o F
Included Accessories:	12 color coded tips to various injection rates
Replacement Parts:	Replacement Tip Kit - part #: P806




VENTURI PROPORTIONER

Tip Color	Injection Range Based On Pressure
Red	1.1% @ 7 PSI to 0.6% @ 58 PSI
Orange	1.2% @ 7 PSI to 0.7% @ 58 PSI
Black	2.2% @ 7 PSI to 1.2% @ 58 PSI
Light Green	2.6% @ 7 PSI to 1.5% @ 58 PSI
Yellow	3.5% @ 7 PSI to 2.1% @ 58 PSI
Brown	6.0 % @ 7 PSI to 3.6% @ 58 PSI

Tip Color	Injection Range Based On Pressure
Dark Green	7.7% @ 7 PSI to 4.5% @ 58 PSI
White	10.4% @ 7 PSI to 6.6% @ 58 PSI
Blue	15.3% @ 7 PSI to 10.6% @ 58 PSI
Purple	21.2% @ 7 PSI to 15.5% @ 58 PSI
Gray	32.8% @ 7 PSI to 22.4% @ 58 PSI
Tan	34.8% @ 7 PSI to 23.0% @ 58 PSI
No Tip	37.0% @ 7 PSI to 26.0% @ 58 PSI

NOTE: These results were obtained injecting water. Product viscosity will change these rates.

- The higher the viscosity, the lower the injection rate
- The higher the pressure, the lower the injection rate
- Constant pressure and flow conditions are required to obtain repeatability (constant injection results over time)



Dosatron International 2090 Sunnydale Blvd. • Clearwater, FL, USA 800-523-8499 • www.dosatronusa.com